

11/07/00

A

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)*(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.
97-1165Total Pages in this Submission
50**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

PBR WITH TECH BYPASS AND WET DISCONNECT/CONNECT FEATURE

and invented by:

David Cameron	Lindley Baugh
Russell Miller	Rustom Mody
Robert Smith	Robert Coon
Walter Myron	Michael Carmody

If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 14 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☒ Cross References to Related Applications *(if applicable)*
 - c. ☐ Statement Regarding Federally-sponsored Research/Development *(if applicable)*
 - d. ☐ Reference to Microfiche Appendix *(if applicable)*
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings *(if drawings filed)*
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

11/06/00

USPTO

**UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.
97-1165Total Pages in this Submission
50**Application Elements (Continued)**

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☐ Formal Number of Sheets _____
- b. ☒ Informal Number of Sheets 19
4. ☐ Oath or Declaration
- a. ☐ Newly executed *(original or copy)* ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☐ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☒ Information Disclosure Statement/PTO-1449 ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class ☒ Express Mail *(Specify Label No.):* EL564088817US

(Only for new nonprovisional applications¹ under § 37 CFR 1.53(b))

Total Pages in this Submission
50

An applicant who makes a request not to publish, but who subsequently files in a foreign country or under a multilateral international agreement specified in 35 U.S.C. 122(b)(2)(B)(i), must notify the Director of such filing not later than 45 days after the date of the filing of such foreign or international application. A failure of the applicant to provide such notice within the prescribed period shall result in the application being regarded as abandoned, unless it is shown to the satisfaction of the Director that the delay in submitting the notice was unintentional.

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
97-1165

Total Pages in this Submission
50

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	68	- 20 =	48	x \$18.00	\$864.00
Indep. Claims	7	- 3 =	4	x \$80.00	\$320.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$710.00
OTHER FEE (specify purpose) _____					\$0.00
TOTAL FILING FEE					\$1,894.00

- ☐ A check in the amount of _____ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 02-0429 as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of \$1,894.00 as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: November 6, 2000

Keith J. Murphy
Registration No. 33,979



23413

CC:

PATENT TRADEMARK OFFICE

Express Mail Label #EL564088817US

PBR WITH TEC BYPASS AND WET DISCONNECT/CONNECT FEATURE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application Serial No. 60/163,575 filed November 5, 1999, which is incorporated herein by reference.

5 BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to downhole electrical connections made up in a wet environment. More particularly, the invention relates to downhole sealed connectors which self-clean upon makeup to avoid contamination in the connection.

10 Prior Art

Downhole power/signal wire connection/disconnection has always been a problem for the industry. More specifically, because the downhole environment is extremely hostile to electric connection (salt water, fresh water, acids, etc.), it has traditionally been thought that a reliable "wet connection" could not be effected. Prior art systems have attempted to create wet connection that employ in the downhole environment but have met with only limited reliability. The prior art connectors are quite small and require an unlikely degree of precision when the connection is to be made, for example, 5000 feet below the surface. Therefore, although these connectors are reasonably capable of providing a good electrical connection at the surface in modern wellbore systems, they fail to solve the need for connection of an uphole string to a downhole string far below the surface. Such connections are required for the plurality of tools incorporated which require power and instructions.

25 SUMMARY OF THE INVENTION

The above-discussed and other drawbacks and deficiencies of the prior art are

overcome or alleviated by the wet connector/disconnector embodiments of the invention.

All of the embodiments of the invention avoid the need to stab-in a small connector. The stabbing-in of the tubing itself is all that is necessary to make up the connection. This is a substantial benefit to the art in view of the growing use of electrically activated downhole tools. The wet connect/disconnect ensures reliability of such systems due to an increase in the likelihood of connection and a reduction in the care needed to effect the connection.

Most of the embodiments disclosed herein employ an insulator that protects a conductor installed with the downhole equipment. The insulator may be rubber, plastic, metal, a grease, etc. with the joining principal being to maintain the conductor in a very clean condition. Additionally, some of the embodiments further include a hydraulic fluid wash to ensure the conductor does not become contaminated when the insulator is pierced or otherwise removed by the string/connector being stabbed in. Generally, the conductor on the stab-in tool is also protected by one or more of the insulators noted above.

Other embodiments do not employ conductor insulators on the downhole string but rely upon a cleansing action of the uphole string upon stab-in to remove any debris or oxidation that may have accumulated on the downhole conductors.

With each of the embodiments disclosed herein, the process of stabbing in causes certain events to occur which lead to secure reliable connections.

In addition to the ability to wet connect, some of the embodiments herein allow for a wet disconnect and reconnect which is advantageous for situations requiring such activity. In one embodiment, a portion of the uphole string is left connected to the downhole string. This leaves the connection made during stabbing-in undisturbed. Rather a piece of the uphole section, which itself provides a new insulated conductor (or not insulated) for a subsequent stab-in procedure, is left behind. Thus, in the event that the uphole section of string needs to be pulled, a reconnection may be made at a later time in the same manner as the original conductor mating. In order to be able to leave a section downhole, a switch section must also be employed to break the connection with the upper string. The switch

section must break the connection in a sealed environment to prevent a short circuit upon reconnecting the uphole string.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings wherein like elements are numbered alike in the several FIGURES:

FIGURE 1 is a schematic elevation view of the concept of the invention;

FIGURE 2 is an enlarged view of a specific embodiment for circumscribed portion A of FIGURE 1;

FIGURE 3 is an enlarged view of an alternate specific embodiment for circumscribed portion A;

FIGURES 4A and 4B are a top and bottom portion of an alternate connection apparatus for the circumscribed portion A in FIGURE 1 in a non-connected position;

FIGURES 5A and 5B are a top and bottom portion of the embodiment of FIGURE 4A and 4B in a connected position;

FIGURES 6 A and 6B are disconnected and connected views, respectively of another alternate embodiment for the circumscribed section A in FIGURE 1;

FIGURE 7 is another alternate embodiment for the circumscribed section A in FIGURE 1;

FIGURES 8A and 8B are disconnected and connected views respectively of another alternate embodiment for the circumscribed section A in FIGURE 1;

FIGURES 9A and 9B are an embodiment of the circumscribed area B in FIGURE 1;

FIGURES 10A-C are various positions of an alternate embodiment of the circumscribed section B in FIGURE 1;

FIGURES 11-13 are an elongated quarter-section view of the tool of this embodiment of the invention to illustrate the disassembled condition;

FIGURES 14-17 are together an elongated quarter-section view of another connector tool of the invention;

FIGURE 18 is a cross section view of the portion of the invention illustrated in FIGURE 11 taken along section line 15-15; and

FIGURE 19 is a cross section view of the portion of the invention illustrated in FIGURE 12 taken along section line 16-16.

DETAILED DESCRIPTION OF SEVERAL PREFERRED EMBODIMENTS

Referring to FIGURE 1, a schematic illustration provides an understanding of the disclosure in its broadest sense without details on the specific mechanisms of operable models. It will be understood that many different embodiments are possible which are capable of being employed to effect the desired results aforesaid. Each of the FIGURES following FIGURE 1 illustrate small sections of FIGURE 1 to teach one of skill in the art a way of connecting or disconnecting the circumscribed areas A or B of FIGURE 1. It is also to be appreciated that in many instances in this specification reference is made to “electrical” or “electrically”; this terminology is for exemplary purposes only and it is intended that the reader understand that other conductors such as fiber optic conductors and light could also be employed.

The broad concept begins with the manufacture of a connection device capable of being installed in a wellbore in various ways and connected to various other devices. Figure 1 illustrates schematically, a connection device in a wellbore. In Figure 1, a lower (first) section of wellbore has been completed with (or from the stand point of manufacture is completable with) a tool string 12 having one or more electrically actuated or controlled tools which may have sensors, etc. This lower section 12 is for any number of reasons, which are known to those of skill in the art, isolated from an upper (second) section of tubing string 14. For this reason, providing an electrical connection between the upper section 14 and lower section 12 is needed.

As noted above, such connections have been difficult in the prior art because of the harsh downhole environment. This disclosure therefore, provides a system for such connection by excluding the downhole fluids from the section 12 conductors (or cleaning them) and ensuring that contaminants do not become introduced thereto during connection. Lower section 12 includes associated wires (or fibers) 16 (one or more) which are connected at the factory to conductor pads (connector) 18.

Conductor pads 18 are generally embedded in the tubing and will include a seal thereover to prevent contamination. Lower section 12 is run in the hole or otherwise

disposed downhole in this condition and will remain in a sealed condition with respect to the pads 18 until an upper section 14 is run in the hole to make a connection with pads 18. Exactly how the pads are connected is discussed hereunder.

It will be appreciated in the FIGURE 1 illustration that another distinct part is illustrated between lower section 12 and upper section 14. This is reconnect (third) section 20. Reconnect section 20 is optional to operability of the system with respect to the original connection. It should be appreciated from a review of FIGURE 1 that the features of lower section 12 are duplicated in reconnect section 20. Thus, it will be understood that upper section 14 might only contain features sufficient to mate with lower section 12 and avoid reconnect section 20. In a preferred embodiment, however, reconnect section 20 is included. Section 20 provides features that substitute for the second connector with respect to connection to the first connector. The section allows for the original connection to remain intact if the upper section 14 is pulled for some reason. This prevents contamination of the conductor pads 18. By way of explanation, once the conductor pads 18 are freed from the insulation that protects them (in this type of embodiment) by the action of stabbing in the uphole section, they are left unprotected from the elements. With the upper section attached, no environmental fluid can contact the pads. If the upper section is pulled however, the conductors would be subject to attack by wellbore fluids. Reconnecting to these conductor pads would be unlikely to succeed. For this reason reconnect section 20 is employed. Continuing now with the discussion of section 20, the section includes a disconnect for the wires in the upper section 14 so that the termination of electrical continuity caused by the pulling of section 14 does not allow a "live" connection to contact downhole fluids. This is important to prevent damage to downhole electrical tools or destruction of the system upon reconnect. The disconnection area is schematically illustrated by circumscribed area B in FIGURE 1.

Reconnect section 20 is solely provided to create a stacked system capability. More specifically, reconnect section 20 is connected at the factory to the upper section 14 with a shearable or otherwise releasable connection to upper section 14. In the event upper section 14 must be removed from the hole, it leaves in its wake, reconnect section 20 which includes new sealed connector pads 18' and wires 24

which connect to the original stab in connectors 26. A subsequent upper section may then be stabbed into the reconnect section with the same reliability as the original connection the concept of the reconnect section may be employed over and over again as many times as a disconnect and reconnect are necessary. The reconnect sections simply continue to stack up as strings are pulled and reconnected.

Turning now to specific mechanisms, circumscribed area A is discussed first and is directed to several embodiments for creating a clean electrical connection with reliability and high confidence. In these FIGURES, only the connection mechanism is illustrated. It is to be understood that the mechanism is part of section 14 or section 20 as desired. Following the discussion of area A, circumscribed area B is discussed. Area B is directed to embodiments for breaking the connection with the wires 22 of section 14 when that section is pulled.

Referring to FIGURE 2, a cover 30 illustrated herein as plastic, but which may be rubber or metallic, is positioned in a sealed relationship over conductor 18. Thus, while this portion of lower section 12 is exposed to wellbore fluid, the conductor 18 is protected. The connection mechanism which is shown in place after run in but before actuation, includes a bore 34, preferably filled with hydraulic fluid 30 (or similar). A wedge 38 is provided in the bore 34 which is driven like a piston preferably by pressure from a proximate or remote source into contact with electrical connector 40 connected with wire 44 from the upper section. Electrical connector 40 includes a ramped surface 46 and a punch 48. Ramped surface 46 is complementary to wedge 38 and connector 40 is urged thereby toward seal material 42. Continued urging of connector 40 results in piercing of seal 42. Upon the piercing of seal 42, fluid 36 escapes from bore 34, flooding the area between seal 42 and seal 30. The flooding action displaces wellbore fluids and provides a clean dielectric embodiment in which the connection can be made. Continued urging of connector 40 causes the punch 48 to pierce seal 30 and come into electrical contact with conductor pad 18. It should be noted that fluid 36 may preferably be dielectric fluid or a dielectric grease. The grease is preferred due to its viscosity and therefore its tendency to remain around the connection.

Referring now to FIGURE 3, an alternate connection mechanism is illustrated.

This mechanism, it will be appreciated, is very similar to the embodiment of FIGURE 2 and merely adds seals 50 which are preferably chevron type seals. For clarity, the other parts of this embodiment, though slightly different in some respects are numbered identically to FIGURE 2. The FIGURE 3 embodiment provides

5 additional, if redundant, assurance of the continued cleanliness of the connection area.

Seals 50 do not allow fluid to pass in either direction whereas seal 50' allows fluid to pass in only the "out" direction relative to the space defined by seals 50, 50'. Thus, the movement of the cleansing fluid 36, which in this embodiment is preferably hydraulic fluid, will sweep all remnants of well fluids out of the connection space and

10 provide a clean connection area.

Referring to FIGURES 4A, 4B and 5A, 5B another alternate embodiment of the invention is illustrated. Because of the relative complexity of the embodiment, it is illustrated in both a nonconnected and connected form, FIGURES 4A, 4B and 5A, 5B, respectively.

15 Referring first to FIGURES 4A and 4B, lower section 12 will provide a reference. This embodiment functions by sliding the upper section, or reconnect section if so equipped, relative to the lower section 12' against spring biased rings which cover the conductor pads. Lower section 12 of this embodiment includes spring 60 based upon land 62 which biases ring 64 to a position where it covers pad

20 18. Section 12' also includes preferably two o-rings 66, which seal against ring 64, and a wiper 68. Section 14', or 20' if so equipped, includes spring 70 which rests on spring stop 72 and biases ring 74 to a position covering conductor pad 76. Ring 74 is sealed over conductor pad 76 by o-rings 78 mounted in ring 74. Conductor pad 76 is preferably spring loaded by springs 80 so that it will be biased against conductor pad

25 18 when so positioned.

An astute reader, skilled in the art, will recognize that there is a volume 82 that likely is contaminated, and that this volume might be problematic to the connection even in view of wiper 68. To eliminate this possibility, the inventors hereof have provided an enclosed hydraulic fluid reservoir 84 which opens via a

30 rupture disk 86 to volume 82. A piston 88 is provided which is operably connected to reservoir 84 and positioned such that the "sliding past" of this embodiment as

discussed above causes piston 88 to move into reservoir 84 increasing pressure therein until rupture disk 86 fails and hydraulic fluid is expelled into volume 82. The hydraulic fluid will displace any wellbore fluids in the volume 82 and render the area clean.

5 In operation, piston 88 lands on ring 64 and expels the hydraulic fluid as discussed. Once piston 88 is fully depressed into the bore of reservoir 84, shoulder 90 begins to urge ring 64 downhole by over coming the bias of spring 60. Next, ring 74 comes into contact with shoulder 92 of section 12' and is urged uphole by overcoming the spring 72 with downhole movement of the upper section or the reconnect section
10 as the case may be.

Conductor pad 76 is uncovered at the time it reaches wiper 68 and is wiped clean to remove any oxidation that may have developed over time. Continued downhole movement of the uphole section aligns conductor pads 18 and 76 and the connection is complete.

15 FIGURE 5A and 5B illustrate this embodiment in the connected condition to promote understanding of the invention.

Referring now to FIGURES 6A and 6B, yet another alternative mechanism for the circumscribed area A in FIGURE 1 is illustrated. The lower section of the drawing is an alternative configuration of section 12 and thus is identified as 12". The
20 conductive pads also differ in appearance and thus are designated 18". The upper section 14" (it should be understood that the upper section of the FIGURE could also be the reconnect section) includes a fluid-filled chamber 100 having an exhaust port 102 sealed by a one-way valve 103 and a rupture disk 104. The chamber 100 is sealed at its other end by seal 106. In a preferred arrangement several o-ring seals are
25 also supplied and are identified by 108. Focusing on the portion of upper section 14" that defines chamber 100, it will be noted that two wipers 110 are provided. One wiper would be effective but two is preferred for redundancy and better cleaning. Contact pads 112 are provided in this area and are protected by fluid 114 in chamber 100.

30 In use, nose 116 of section 12" is urged into seal 106 ultimately rupturing the seal. since o-rings 108 will prevent fluid 114 from escaping around nose 116, the

fluid instead becomes pressurized. As the pressure in chamber 100 increases, burst disk 104 ruptures and fluid 114 is conveyed through the valve 103 to the tubing I.D. Since valve 103 will not permit fluid to pass in the other direction, the connection area in the chamber 100 will remain clean. Continued movement of nose 116 into
 5 chamber 100 brings pads 18" into wiping contact with wipers 110 where the conductor pads 18" are cleaned of any oxides that have formed thereon. The pads 18" then align with pads 112 and the connection is made as illustrated in FIGURE 6B.

FIGURE 7 is another alternative embodiment relating to circumscribed area A is illustrated. In this embodiment the upper section provides a connector 120 which is
 10 composed of a low temperature melt metal (obviously, melting temperature must be above well temperature at projected depth). The metal connector 120 is positioned adjacent conductor pad 18 and includes a coil 122 proximate thereto, the proximity being sufficient to melt the connector 120. As in previous embodiments, seals 134, 132 are provided and a reservoir 128 includes fluid 130 actuated by a piston 126 to
 15 flush the contact area. In this embodiment a surface actuated current or a downhole actuated current melt the connector 120 which then flows into electrical contact with conductor pad 18.

In another alternate embodiment for circumscribed Section A, referring to FIGURES 8A and 8B lower section 12 includes two conductor pads 18. The upper
 20 section of the drawing which again can be the equivalent of section 14 or section 20 in FIGURE 1 depending upon whether a reconnect option after a pull-out is to be provided, provides a nose 130 with several seals 132 of preferably the chevron type. Attached to nose 130 by a release mechanism, preferably a shear pin 134, is connector wedge 136 which houses a piercing conductor pad 138 in fluid 140 under seal 142.
 25 Upon downward movement of the upper section of the drawing (14 or 20) a spring 144 is urged against a ring 146 to move the same downhole until it contacts landing 148 of counter wedge 150. Further downward movement causes counter wedge 150 to move downhole behind connector wedge 136 to cause conductor pads 138 to pierce cover 142 and come into contact with conductor pads 18 to complete the circuit.

30 As discussed above, in the event upper section 14 is removed from the hole, the connections must be broken to prevent a short circuit. This is, for illustrative

purposes, at the area marked B on FIGURE 1. It is important to note that just stretching the connectors to break leaves them exposed to wellbore fluids and invites short circuit. Therefore the inventors hereof have provided the following two embodiments of disconnects. It is to be understood, however, that other mechanisms for providing such a disconnect are clearly within the scope of the invention.

Turning now to FIGURES 9A and 9B, the first disconnect embodiment is illustrated in the connected position and the disconnected position. The disconnect itself comprises a connector pad 162 disposed atop an insulator 160 in a recess 172 in section 12. The recess 172 is sealed by cover 168 which may be of a plurality of distinct materials so long as they either deflect or allow a sealed sliding of the pins 166 therethrough. In the case of deflection, the pins 166 need not slide through cover 168 (the non-sliding arrangement being illustrated herein).

As one can readily ascertain from the drawings, pins 166 provide a base for pads 164, the pins extending to outside cover 168 and into connection with plate 170.

The disconnect is connected together in the factory and appears as illustrated in FIGURE 9A. When a disconnect is desired, pulling the tool causes the switch to be in the condition illustrated in FIGURE 9B wherein the electrical connection is broken and the ends of the downhole wires are protected within recess 172 and cover 168. It will be apparent to one of skill in the art that if upper portion 174 of the drawings is to be removed altogether the disconnect will have to shear at a point above the cover 168. Alternatively, the portion 174 could simply be a ring which remains downhole.

Referring now to FIGURES 10A, 10B and 10C a second disconnect embodiment is illustrated. This disconnect is intended to work in much the same way that the embodiment of FIGURES 9A 9B works and thus only the distinctions are discussed here. Contact bar 180 is connected to an uphole piece of the pipe and supports actuator pin 182 and contact pins 184. Pin 182 includes a wedge 186 which is angled sufficiently to actuate slide 190 through slide pitch 188. Actuation of slide 190 moves it (to the right in the drawing) to align ports 192 with contact receptacles 194 wherein contact pads 196 are disposed and connected to wires 198. Once alignment as described is complete, pins 184 may come into electrical contact with pads 196 (pads 196 are insulated from the metallic tool by insulation 200).

The length of the pins 182 and 184 is important to the operation of the invention. Upon disconnecting, it is required that the slide 190 be closed (under bias of spring 204) prior to pins 184 pulling free from membrane 202. By so requiring, the breach in the seal of membrane 202 due to the pins 184 being extended therethrough is not able to allow contamination into receptacles 194. Obviously it is intended that slide 190 make sealing contact with the surrounding area. This embodiment is made up in the factory preferably but is also useable in the field because of the ability of pin 182 to actuate slide 190 in a time frame where the pins 184 will protectively be in membrane 202.

In yet another embodiment of the invention wherein conductors are aligned and connected. Referring initially to FIGURES 11-13 a more schematic view of the invention is illustrated. The view does not contain all of the parts of the invention and thus is intended to convey the locations and orientation of the connectors. Tool 10 breaks down to a top half (comprising FIGURES 11 and 12) and a bottom half comprising FIGURE 13. When the halves are separated as illustrated in FIGURES 11-13, lower seal adapters 212 (twelve of them on the embodiment shown although more or fewer could be employed) are visible on bottom half (FIGURE 13) and the complementary upper seal adapters 214 (an equal number to the number of lower seal adapters 212). Upper seal adapters 214 preferably include a pair of o-rings 270 to fluid tightly seal the lower seal adapters. Upper seal adapters 214 are connected to the uphole environment via conduits 218 while at the other end of the connection, lower seal adapters 12 are connected to the downhole environment via conduit 20. The conduits 218 and 220 preferably contain fiber optic conductors. The mating ends of the conductors are cleaned by preferably a hydraulic fluid which may be applied in a number of ways including adaptations of the embodiments preferably does not include threads between the alignment profile and end connections.

Although the top and bottom portions of the tool are run in the hole together (assembled at the surface), an alignment profile 222 is provided in the tool to align the top and bottom halves in the event that they are separated. Therefore, referring directly to FIGURES 12 and 13, a profile 224 is a raised area in a predetermined orientation on the anchor sub 226. The profile 224 mates with a complementary

profile 228 in bottom half (FIGURE 13). The orientation profiles ensure that the lower seal adapters 212 will align and mate with upper seal adapters 214 reliably.

Turning now to the internal components of this embodiment of the invention, referring to FIGURES 14-19, and beginning at the uphole end of the tool, a box thread 230 is provided to attach the tool to a work string (not shown). The box thread 230 is cut in body 232 which extends downhole to threadedly mate with anchor sub 234 at thread 236. Body 232 supports, near the uphole end thereof, disc spring retainer cap 238 which is threaded to the O.D. of body 232 at thread 240. Cap 238 is further preferably anchored by cap screw 242. Cap 238 functions to retain preferably a plurality of disc springs (belleville washers) 244. Springs 244 absorb longitudinal movement of upper and lower seal adapters. Moreover, the washers keep the upper and lower seal adapters positively shouldered internally which is important for pump down, replaceable optic fiber installation and other installations. Disc springs 244 are maintained in position at the downhole end by retainer sub 246. Sub 246 is annular and is threaded to disc spring adjustment sub 248 at thread 250.

Downhole of attachment sub 248 and radially outwardly of body 232 is upper connector 252. Upper connector 252 houses upper seal adapters 214 at the downhole end thereof and a line connector assembly 254 which preferably comprises a pair of ferrules and a jam nut (not individually shown). The connector 252 is retained in position on body 232 by shear screw 256 and shoulder screw 258. These latter screws are best viewed in FIGURE 18. A plurality of bores 260 are provided in upper connector 252 to receive conduit 218. Lower connector 262 (FIGURES 15 and 19) is disposed downhole of upper connector 252 and houses lower seal adapter 212, bore 264 for conduit 220 and a control line connector 260 which comprises a pair of ferrules and a jam nut (not individually shown). It should be noted that FIGURE 15 provides a cross section view of the tool which shows the upper and lower seal adapters that were explained previously herein. It should also be noted that upper seal adapter 214 includes two sets of o-rings 268 and 270. Rings 268 seal upper seal adapter 214 to upper connector 252 while rings 270 seal the lower seal adapter 212 into the upper seal adapter 214 when it is so engaged. Lower adapter 212 may be for

conventional conductors or fiber optic conductors. FIGURE 19 illustrates three of four (212a) in conventional form and one (212b) in fiber optic form .

Bridging FIGURES 15 and 16 is sleeve 272 which covers the components of the snap in/snap out feature of the invention (components discussed hereunder).

- 5 Sleeve 272 is connected to seal housing 274 which includes locking dogs 276. Seal housing is also threaded at 278 for a body lock ring 280. The lock ring 280 is rotationally arrested by roll pin 236. Seal housing 274 is sealed to anchor sub 234 by seal stack 281.

- 10 Radially outwardly of seal housing 274 (FIGURES 16 and 17) are housing 282 and control line sub 284. Housing 282 includes several seals 286, several screws 288 and a dog receiving profile 290.

- 15 Radially inwardly of sleeve 272 (FIGURE 16) is the snap in/snap out assembly mentioned above. The assembly includes, beginning from the uphole end, a shear ring retainer 292 which is connected to the anchor sub 234 by shear ring 294. Shear ring retainer 292 is also connected to support ring 298 through set screws 296 and thread 300. Support ring 298 supports set down sleeve 302 and is in contact with body lock housing 306. Body lock ring housing 306 is connected to body lock ring 304 conventionally and including a set screw 308 to arrest rotational movement. Body lock ring housing 306 is also threadedly connected to set down sleeve 302 by
20 thread 310. Body lock ring housing 306 cannot move up or downhole because of shear screw 312 which engages anchor sub 234. Body lock ring housing 306 is connected to latch 314 by parting ring 316 which is a ring having holding profiles 318 to retain the body lock ring housing 306 to latch 314 until a predetermined tensile load is placed thereon which breaks the parting ring 316.

- 25 In operation and after running in the hole, a pressure line 243 (FIGURE 16) pressurizes a piston area 318 sealed by seals 86. Upon reaching a predetermined pressure, shear screw 288 shears and allows housing 282 to move downhole thus locating recess 290 over locking dogs 276 allowing them to move radially outwardly to disengage from anchor sub 234. Once anchor sub 234 is disengaged from the dogs
30 276 it will be free to move. Body lock ring 280 is provided to prevent housing 282 from moving back uphole and reseating the dogs 276. After initial setting then, the

housing portion of the tool is permanently moved and the dogs 276 are permanently disengaged from anchor sub 234. Following this disengagement, the tool upper portion (FIGURES 11 and 12) and lower portion (FIGURE 13) are separable using the snap in/snap out assembly in order to develop a proper space-out for the particular well, the tool may be snapped in/snapped out as many times as necessary until sufficient weight is committed and the anchor sub 234 supports the latch 314. In this latter condition the snap out feature is disabled.

Once the space out is appropriate, set down weight which exceeds the shear strength of shear ring 294 and shear screw 312 is applied. After shearing, anchor sub 234 moves downhole through lock ring 304 and is retained in this position until retrieval is necessary or desired.

In order to retrieve the tool, a tensile load is placed on the anchor sub which transmits to the body lock ring 304, the parting ring 316 and the latch 314. When a predetermined tensile load is exceeded, the parting ring fails and the anchor sub 34 moves uphole. This unsupports latch 314 allowing the latch to deflect into recess 320 and the snap out sub is operational. Continued tensile load will disengage the upper portion of the tool from the lower portion for retrieval. The process as described can then be repeated with a new or rebuilt upper portion.

While preferred embodiments have been shown and described, various modifications and substitutions may be made thereto without departing from the spirit and scope of the invention. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.

What is claimed is:

CLAIM 1. A conductor connection device for a downhole environment comprising:

a first section connectable to implements intended to be located farther downhole than said first section when said device is installed in a wellbore;

5 at least one first conductor associated with said first section;

a first connector in operable communication with said at least one first conductor, said first connector being maintained in a clean condition or being cleanable by operation of the connection device;

10 a second section connectable to implements intended to be located farther uphole than said second section when said device is installed in a wellbore;

at least one second conductor associated with said second section;

a second connector in operable communication with said at least one second conductor, said second connector being maintained in a clean condition or being cleanable by operation of the connection device, said second connector being
15 connectable to said first connector by operation of said connection device.

CLAIM 2. A conductor connection device as claimed in claim 1 wherein said connection device further comprises:

a third section connectable to said second section prior to being run downhole to substitute for functions of the second section related to the second connector and

5 releasable from said second section after connection with said first section;

at least one third conductor associated with said third section;

a third connector in operable communication with said at least one third conductor, said third conductor also being in operable communication with said at least one second conductor, said third conductor being maintained in a clean

10 condition or cleanable by operation of said connection device;

said third connector being connectable to said first connector by operation of said connection device;

a forth connector in operable communication with said at least one third conductor, said forth connector being maintained in a clean condition or being

15 cleanable by operation of a subsequently run connection device.

CLAIM 3. A conductor connection device as claimed in claim 1 wherein said first connector and said second connector each comprise:

at least one pad;

at least one fluid impermeable covering on each said at least one pad.

CLAIM 4. A conductor connection device as claimed in claim 3 wherein said connection device further includes at least one interconnector providing interconnection between said first connector pad and said second connector pad.

CLAIM 5. A conductor connection device as claimed in claim 4 wherein said interconnector is a conductive piercing member which pierces said at least one fluid impermeable covering on each said at least one pad upon operation of said connection device.

CLAIM 6. A conductor connection device as claimed in claim 1 wherein said connection device is configured to provide a dielectric material to a vicinity of interconnection between said first connector and said second connector.

CLAIM 7. A conductor connection device as claimed in claim 5 wherein said covering is rubber.

CLAIM 8. A conductor connection device as claimed in claim 5 wherein said covering is metal.

CLAIM 9. A conductor connection device as claimed in claim 6 wherein said dielectric material is oil.

CLAIM 10. A conductor connection device as claimed in claim 6 wherein said dielectric material is grease.

CLAIM 11. A conductor connection device as claimed in claim 1 wherein said first connector and said second connector are exposed to environmental conditions and are wiped clean during operation of the connection device.

CLAIM 12. A conductor connection device as claimed in claim 11 wherein said device is configured to provide a dielectric material to an interconnection vicinity of said connection device.

CLAIM 13. A conductor connection device as claimed in claim 12 wherein said dielectric material is oil.

CLAIM 14. A conductor connection device as claimed in claim 12 wherein said dielectric material is grease.

CLAIM 15. A conductor connection device as claimed in claim 12 wherein said dielectric material is dispensed from a reservoir in said device.

CLAIM 16. A conductor connection device as claimed in claim 11 wherein said first connector and said second connector are wiped clean by each other.

CLAIM 17. A conductor connection device as claimed in claim 11 wherein said first connector and said second connector are wiped clean by a wiper.

CLAIM 18. A conductor connection device as claimed in claim 15 wherein said reservoir includes a check valve.

CLAIM 19. A conductor connection device as claimed in claim 1 wherein said first connector is a pad and said second connector includes a meltable conductive element.

CLAIM 20. A conductor connection device as claimed in claim 19 wherein said element is meltable by a coil.

CLAIM 21. A conductor connection device as claimed in claim 20 wherein said coil is powered from within said device.

CLAIM 22. A conductor connection device as claimed in claim 20 wherein said coil is powered from external to said device.

CLAIM 23. A conductor connection device as claimed in claim 1 wherein said device is configured to provide a dielectric material to an area of interconnection of said first connector and said second connector.

CLAIM 24. A conductor connection device as claimed in claim 23 wherein said dielectric material is oil.

CLAIM 25. A conductor connection device as claimed in claim 23 wherein said dielectric material is grease.

CLAIM 26. A conductor connection device for a downhole environment comprising:

a first section connectable to implements intended to be located farther downhole than said first section when said device is installed in a wellbore;

at least one first conductor associated with said first section;

a first connector in operable communication with said at least one first conductor, said first connectors being maintained in a clean condition or being cleanable by operation of the connection device;

a second section connectable to implements intended to be located farther uphole than any said second section when said second section is installed in a wellbore;

at least one second conductor associated with said second section;

a third section operably connected to said second section ;

at least one third conductor associated with said third section, said at least one third conductor being operably connected to said at least one second conductor;

a third connector in operable communication with said at least one third conductor, said third connector being maintained in a clean condition or being cleanable by operation of the connection device, said third connector being connectable to said first connector by operating said connection device, said third section being separable from said second section after said connection device is operated;

a forth connector in operable communication with said at least one third conductor, said forth connector being maintained in a clean condition or being cleanable by operation of a subsequent connection device.

CLAIM 27. A conductor connection device as claimed in claim 26 wherein said third section further comprises a conductor break to prevent conductive contact of said at least one first conductor through said at least one third conductor with wellbore fluids upon separation of said third section from said second section.

CLAIM 28. A conductor connection device as claimed in claim 27 wherein said conductor break comprises at least two contacts maintained in a clean environment, said contacts being separable upon separation of said second section.

CLAIM 29. A conductor connection device as claimed in claim 28 wherein said clean environment is maintained by a deflectable cover to which one of said at least two contacts is connected, said deflectable cover being deflected to maintain connection of said at least two contacts while said third section is attached to said second section.

CLAIM 30. A conductor connection device as claimed in claim 27 wherein said conductor break comprises:

- at least one contact pin; and
- at least one contact receptacle.

CLAIM 31. A conductor connection device as claimed in claim 30 wherein said break further comprises a slide which seals said at least one receptacle when said at least one pin is not engaged in said at least one receptacle.

CLAIM 32. A conductor connection device as claimed in claim 31 wherein said break further includes an actuator pin to actuate said slide.

CLAIM 33. A conductor connection device as claimed in claim 26 wherein said first connector and said third connector each comprise:

- at least one pad;
- at least one fluid impermeable covering on each said at least one pad.

CLAIM 34. A conductor connection device as claimed in claim 33 wherein said connection device further includes at least one interconnector providing interconnection between said first connector pad and said third connector pad.

CLAIM 35. A conductor connection device as claimed in claim 34 wherein said interconnector is a conductive piercing member which pierces said at least one fluid impermeable covering on each said at least one pad upon operation of said connection device.

CLAIM 36. A conductor connection device as claimed in claim 26 wherein said connection device is configured to provide a dielectric material to a vicinity of interconnection between said first connector and said third connector.

CLAIM 37. A conductor connection device as claimed in claim 35 wherein said covering is rubber.

CLAIM 38. A conductor connection device as claimed in claim 35 wherein said covering is metal.

CLAIM 39. A conductor connection device as claimed in claim 36 wherein said dielectric material is oil.

CLAIM 40. A conductor connection device as claimed in claim 36 wherein said dielectric material is grease.

CLAIM 41. A conductor connection device as claimed in claim 26 wherein said first connector and said third connector are exposed to environmental conditions and are wiped clean during operation of the connection device.

CLAIM 42. A conductor connection device as claimed in claim 41 wherein said device is configured to provide a dielectric material to an interconnection vicinity of said connection device.

CLAIM 43. A conductor connection device as claimed in claim 42 wherein said dielectric material is oil.

CLAIM 44. A conductor connection device as claimed in claim 42 wherein said dielectric material is grease.

CLAIM 45. A conductor connection device as claimed in claim 42 wherein said dielectric material is dispensed from a reservoir in said device.

CLAIM 46. A conductor connection device as claimed in claim 41 wherein said first connector and said third connector are wiped clean by each other.

CLAIM 47. A conductor connection device as claimed in claim 41 wherein said first connector and said third connector are wiped clean by a wiper.

CLAIM 48. A conductor connection device as claimed in claim 45 wherein said reservoir includes a check valve.

CLAIM 49. A conductor connection device as claimed in claim 26 wherein said first connector is a pad and said third connector includes a meltable conductive element.

CLAIM 50. A conductor connection device as claimed in claim 49 wherein said element is meltable by a coil.

CLAIM 51. A conductor connection device as claimed in claim 50 wherein said coil is powered from within said device.

CLAIM 52. A conductor connection device as claimed in claim 50 wherein said coil is powered from external to said device

CLAIM 53. A conductor connection device as claimed in claim 26 wherein said device is configured to provide a dielectric material to an area of interconnection of said first connector and said third connector.

CLAIM 54. A conductor connection device as claimed in claim 53 wherein said dielectric material is oil.

CLAIM 55. A conductor connection device as claimed in claim 53 wherein said dielectric material is grease.

CLAIM 56. A downhole connection device comprising:

at least two connectors on an uphole end of a connection interface;

at least two complementary connectors on a downhole end of said connection interface; and

a self orienting profile within said connection device.

CLAIM 57. A downhole conductor connection device comprising:

a downhole portion including a lower conductor leading farther downhole and an orientation profile;

an uphole portion having a conductor leading farther uphole and a complementary orientation profile;

at least one lower seal adapter connected to said lower conductor; and

at least one upper seal adapter connected to said upper conductor, said lower seal adapter being receivable in said upper seal adapter to connect said lower conductor to said upper conductor.

CLAIM 58. A downhole conductor connection device as claimed in claim 57 wherein said connection device further includes a snap in/snap out thread.

CLAIM 59. A downhole conductor connection device as claimed in claim 57 wherein said device further comprises a dog support system to lock said device in a selected position.

CLAIM 60. A downhole conductor connection device as claimed in claim 59 wherein said dog support system is collapsible upon pressuring a control line to shift a housing.

CLAIM 61. A method for downhole conductor connection comprising:

running a downhole and an uphole connector portion in a sealed engaged condition;

opening said sealed engaged connector;

orientating said uphole connector with said downhole connector; and

reengaging at least one conductor.

CLAIM 62. A method for creating a conductive connection in a downhole environment comprising:

installing a first section connectable to implements located farther downhole from an intended location of said first section, said first section having at least one conductor associated therewith and a connector operably connected to said at least one conductor, said conductor being maintained in a clean condition or being cleanable upon engagement of said first section with a second section;

installing said second section connectable to implements located further uphole than an intended location of said second section, said second section having at least one conductor associated therewith and a connector operably connected to said at least one conductor, said conductor being maintained in a clean condition or being cleanable upon engagement of said first section with said second section, engaging said first section with said second section.

15

CLAIM 63. A method for creating a conductive connection as claimed in claim 62 wherein said engaging includes forming a conductive connection between said first section and said second section.

CLAIM 64. A method for creating a conductive connection as claimed in claim 62 wherein said engaging causes self orientation of said first section and said second section.

CLAIM 65. A method for creating a conductive connection in a downhole environment while providing for disconnection and reconnection comprising:

installing a first section connectable to implements located farther downhole than an intended location of said first section, said first section having at least one
5 conductor associated therewith and a connector operably connected to said at least one conductor;

installing a second section connectable to implements located farther uphole than an intended location of said second section, said second section having at least one conductor associated therewith, said second section further including a third
10 section having at least one conductor associated therewith and a third connector operably connected at one end to said at least one conductor and a fourth connector operably connected at the other end of said at least one connector; and

engaging said third section and said first section

CLAIM 66. A method for creating a conductive connection as claimed in claim 65 further including:

disconnecting said second section from said third section; and

installing a separate second section and engaging said third section in position
5 as connected to said first section.

CLAIM 67. A method for creating a conductive connection as claimed in claim 62 wherein said engaging includes flushing with a dielectric fluid, a connection area of interconnection between said first connector and said second connector.

CLAIM 68. A method for creating a conductive connection as claimed in claim 65 wherein said engaging includes flushing with a dielectric fluid, a connection area of interconnection between said first connector and said third connector.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

ABSTRACT OF THE INVENTION

A wet connect/disconnect arrangement is disclosed for a downhole system that allows installation of various tools and/or a string and subsequent electrical connection to the downhole system in a wet environment. Several embodiments are disclosed, all of which produce a clean, reliable connection.

[illegible]

0000071884140000




FIG 1




FIG 2







FIG 3

③ A
UPPER




④ A
UPPER





4B
LOWER



3B
LOWER

09707165 410600




FIG 6A
— A —

71668

- B -




FIG 7

1D




Fig. 8A





Fig.
— 8B —

516. 28

FIG 10 A



09707468 14000

09707168-110600




FIG 10 B

089707168-110000






Fig 10C

FIG. 11

210



210



224

226




FIG. 12

218

212

212

228

210

20




FIG. 13

0001-88720250




FIG. 14




FIG. 18






FIG. 15



SECTION 'B-B'

FIG. 19



53,57,58

FIG. 16





FIG. 17

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☒ Scanned copy is best available. *drawings*

SCANNED, # 14